



# The Bobcat Dry Van

OPTION-1  
BASE: MATTE SILVER  
LOGO: BLUE/BLACK



## Not Your Average Dry Van

The Bobcat has exceptional stability with our new features. Our composite panel has added sections from the bottom to the top of each panel to support the toughest load requirements, yet still maintaining less weight to maximize payload capacity.

## Exceptional Durability

With the added sections on the interior and exterior sides of the trailer, our newly designed dry van can withstand extreme loading and unloading. The newly designed sections resist exterior and interior sideswipe damages.

## Specifications: The Bobcat Dry Van

<b>General</b>	<ul style="list-style-type: none"> <li>• Dimensions: 53' x 102" x 13'6"</li> <li>• Interior height:</li> <li>• Interior width:</li> <li>• Interior length:</li> <li>• GVWR: 68,000 lbs</li> <li>• GAWR: 20,000 lbs</li> <li>• Manufactured in Lubbock, Texas</li> </ul>
<b>Floor</b>	<ul style="list-style-type: none"> <li>• 4" steel crossmembers on 12" centerline from landing gear to rear</li> <li>• 1<math>\frac{3}{8}</math>" laminated oak wood floor</li> <li>• 2 floor screws per plank per crossmember</li> </ul>
<b>Support Legs</b>	<ul style="list-style-type: none"> <li>• Static load capacity 170,000 lbs</li> <li>• Lifting capacity 60,000 lbs</li> <li>• Side load capacity 29,000 lbs</li> <li>• 17" travel sand shoe</li> </ul>
<b>Front Subframe</b>	<ul style="list-style-type: none"> <li>• 4" steel crossmembers on 6" centerline</li> <li>• High-strength steel continuous king pin plate</li> </ul>
<b>Front wall</b>	<ul style="list-style-type: none"> <li>• .03" aluminum sheets with .08" exterior Stainless steel reinforcement</li> <li>• 4" corner radius post</li> <li>• Same sturdiness as side panels</li> </ul>
<b>Side Wall</b>	<ul style="list-style-type: none"> <li>• .03" aluminum sheets with galvanized steel c-channel reinforcement frame for extra sturdiness</li> <li>• Galvanized steel E-track side posts with 24" centerlines</li> <li>• 15" continuous 18-gauge galvanized steel scuff liner</li> </ul>
<b>Roof</b>	<ul style="list-style-type: none"> <li>• Aluminum I-beam roof bows with 18" centerline</li> <li>• .04" aluminum roof panel</li> <li>• 3.5" aluminum exterior top rail and 2" interior aluminum rail</li> </ul>
<b>Rear Frame</b>	<ul style="list-style-type: none"> <li>• 6" stainless steel door frame</li> <li>• 1.5" composite swing doors</li> <li>• .04" exterior and interior stainless steel door panels</li> <li>• 4-hole stainless steel hinges, four per door</li> <li>• One stainless steel lock rod per door with integral door holdback</li> </ul>
<b>Axle and Suspension</b>	<ul style="list-style-type: none"> <li>• Hendrickson® ULTRAA-40K with integral axles</li> <li>• Air ride/suspension</li> <li>• Quick-Draw® air-operated sliding mechanism</li> <li>• HP spindle steel wheel ends</li> <li>• Hot dip wax with black soft coat surface finish</li> </ul>

<b>Electrical</b>	<ul style="list-style-type: none"><li>• All LED lights</li><li>• Phillips 7-way light harness</li></ul>
-------------------	---